

FORM PTO-1390 REV. 5-93		US DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE	ATTORNEYS DOCKET NUMBER P00,1993
TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371			U.S. APPLICATION NO. (if known, see 37 CFR 1.5) 09/763772
INTERNATIONAL APPLICATION NO. PCT/DE99/01949	INTERNATIONAL FILING DATE 1 July 1999	PRIORITY DATE CLAIMED 25 August 1998	
TITLE OF INVENTION "METHOD FOR TRAINING A NEURAL NETWORK, METHOD FOR CLASSIFYING A SEQUENCE OF INPUT PARAMETERS USING A NEURAL NETWORK, NEURAL NETWORK AND ARRAY FOR TRAINING A NEURAL NETWORK"			
APPLICANT(S) FOR DO/EO/US Gustavo DECO AND Bernd SCHÜRMANN			
Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:			
<ol style="list-style-type: none"> 1. <input checked="" type="checkbox"/> This is a FIRST submission of items concerning a filing under 35 U.S.C. 371. 2. <input type="checkbox"/> This is a SECOND or SUBSEQUENT submission of items concerning a filing under 35 U.S.C. 371. 3. <input checked="" type="checkbox"/> This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay. 4. <input checked="" type="checkbox"/> A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date. 5. <input checked="" type="checkbox"/> A copy of International Application as filed (35 U.S.C. 371(c)(2)) <ol style="list-style-type: none"> a. <input checked="" type="checkbox"/> is transmitted herewith (required only if not transmitted by the International Bureau). b. <input type="checkbox"/> has been transmitted by the International Bureau. c. <input type="checkbox"/> is not required, as the application was filed in the United States Receiving Office (RO/US) 6. <input checked="" type="checkbox"/> A translation of the International Application into English (35 U.S.C. 371(c)(2)). 7. <input checked="" type="checkbox"/> Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. §371(c)(3)) <ol style="list-style-type: none"> a. <input type="checkbox"/> are transmitted herewith (required only if not transmitted by the International Bureau). b. <input type="checkbox"/> have been transmitted by the International Bureau. c. <input type="checkbox"/> have not been made; however, the time limit for making such amendments has NOT expired. d. <input checked="" type="checkbox"/> have not been made and will not be made. 8. <input type="checkbox"/> A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)). 9. <input checked="" type="checkbox"/> An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)). 10. <input type="checkbox"/> A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)). 			
Items 11. to 16. below concern other document(s) or information included:			
<ol style="list-style-type: none"> 11. <input checked="" type="checkbox"/> An Information Disclosure Statement under 37 C.F.R. 1.97 and 1.98; (PTO 1449, Prior Art, Search Report). 12. <input checked="" type="checkbox"/> An assignment document for recording. A separate cover sheet in compliance with 37 C.F.R. 3.28 and 3.31 is included. (SEE ATTACHED ENVELOPE) 13. <input checked="" type="checkbox"/> A FIRST preliminary amendment. <input type="checkbox"/> A SECOND or SUBSEQUENT preliminary amendment. 14. <input checked="" type="checkbox"/> A substitute specification & marked up version of application. 15. <input checked="" type="checkbox"/> A change of power of attorney and/or address letter. 16. <input checked="" type="checkbox"/> Other items or information: <ol style="list-style-type: none"> a. <input checked="" type="checkbox"/> Submittal of Drawings b. <input checked="" type="checkbox"/> EXPRESS MAIL #EL 655301196US, dated February 26, 2001. 			

U.S. APPLICATION NO. (if known, see 37 C.F.R. 1.17)

09/763772

INTERNATIONAL APPLICATION NO.

PCT/DE99/01949

ATTORNEY'S DOCKET NUMBER

P00,1993

17. ☒ The following fees are submitted:**BASIC NATIONAL FEE (37 C.F.R. 1.492(a)(1)-(5):**

Search Report has been prepared by the EPO or JPO \$860.00

International preliminary examination fee paid to USPTO (37 C.F.R. 1.482) .. \$700.00

No international preliminary examination fee paid to USPTO (37 C.F.R. 1.482) but
international search fee paid to USPTO (37 C.F.R. 1.445(a)(2)) \$770.00Neither international preliminary examination fee (37 C.F.R. 1.482) nor international
search fee (37 C.F.R. 1.445(a)(2)) paid to USPTO \$1040.00International preliminary examination fee paid to USPTO (37 C.F.R. 1.482) and all
claims satisfied provisions of PCT Article 33(2)-(4) \$ 96.00**ENTER APPROPRIATE BASIC FEE AMOUNT =**

CALCULATIONS

PTO USE ONLY

\$ 860.00

Surcharge of \$130.00 for furnishing the oath or declaration later than ☐ 20 ☐ 30 months
from the earliest claimed priority date (37 C.F.R. 1.492(e)).

\$

Claims

Number Filed

Number
Extra

Rate

Total Claims

16 - 20 =

X \$ 18.00

\$

Independent Claims

4 - 3 =

1

X \$ 80.00

\$ 80.00

Multiple Dependent Claims

\$270.00 +

\$

TOTAL OF ABOVE CALCULATIONS =

\$ 860.00

Reduction by 1/2 for filing by small entity, if applicable. Verified Small Entity statement must
also be filed. (Note 37 C.F.R. 1.9, 1.27, 1.28)

\$

SUBTOTAL =

\$ 940.00

Processing fee of \$130.00 for furnishing the English translation later than ☐ 20 ☐ 30 months
from the earliest claimed priority date (37 CFR 1.492(f)).

\$

TOTAL NATIONAL FEE =

\$ 940.00

Fee for recording the enclosed assignment (37 C.F.R. 1.21(h). The assignment must be
accompanied by an appropriate cover sheet (37 C.F.R. 3.28, 3.31). \$40.00 per property

+

TOTAL FEES ENCLOSED =

\$ 940.00

Amount to be
refunded

\$

charged

\$

a. ☒ A check in the amount of \$ 940.00 to cover the above fees is enclosed.b. ☐ Please charge my Deposit Account No. _____ in the amount of \$ _____ to cover the above fees. A
duplicate copy of this sheet is enclosed.c. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any
overpayment to Deposit Account No. 501519. A duplicate copy of this sheet is enclosed.**NOTE:** Where an appropriate time limit under 37 C.F.R. 1.494 or 1.495 has not been met, a petition to revive (37 C.F.R. 1.137(a) or (b)) must be
filed and granted to restore the application to pending status.**SEND ALL CORRESPONDENCE TO:**Schiff Hardin & Waite
Patent Department
6600 Sears Tower
Chicago, Illinois 60606

SIGNATURE

Melvin A. Robinson

NAME

31,870

Registration Number

CUSTOMER NO. 26574

"PRELIMINARY AMENDMENT"

An amended substitute specification is attached, and a marked up copy of the original specification showing the changes is also enclosed.

IN THE CLAIMS

Amend the claims as shown in the following replacement claims, the marked up version of which is attached following the marked up specification.

We Claim:

- 5 1. A method for training a neural network that contains pulsed neurons,
- a) training the neural network for a first time span such that a discrimination
value is maximized, as a result whereof a maximum first discrimination
value is formed;
- b) forming the discrimination value dependent on pulses that are formed by
10 the pulsed neurons within the first time span as well as on a training
sequence of input quantities that are supplied to the neural network;
- c) implementing the following steps interactively:
shortening the first time span to form a second time span,
forming a second discrimination value for the second time span,
15 when the second discrimination value is the same as the first
discrimination value, then performing a new iteration with a new second
time span that is formed by shortening the second time span of the
preceding iteration,
otherwise, ending the method and the trained neural network is the neural
20 network of the last iteration wherein the second discrimination value is the
same as the first discrimination value.

2. A method according to claim 1, wherein an optimization method that is not gradient based is utilized for the maximization of at least one of the first discrimination value and of the second discrimination value.

3. A method according to claim 2, wherein the optimization method is based on the ALOPEX method.

4. A method according to claim 1, whereby the first discrimination value $I(T)$ satisfies the following rule:

$$I(T) = I \left(s; \left\{ \begin{array}{l} t_1^{(1)}, \dots, t_m^{(1)}, \dots, t_{k_1}^{(1)}, t_1^{(2)}, \dots, t_m^{(2)}, \dots, t_{k_2}^{(2)}, \dots, \\ t_1^{(n)}, \dots, t_m^{(n)}, \dots, t_{k_n}^{(n)}, \dots, t_1^{(N)}, \dots, t_m^{(N)}, \dots, t_{k_N}^{(N)} \end{array} \right\} \right),$$

5 wherein

- s references the input quantities,
- $t_m^{(n)}$ references a pulse that is generated by a pulsed neuron n at a time m within a time span $[0, T]$,
- k_n ($n = 1, \dots, N$) references a point in time at which the pulsed neuron n has generated the last pulse within the time span $[0, T]$, and
- N references a plurality of pulsed neurons contained in the neural network.

5. A method according to claim 4, wherein the first discrimination value $I(T)$ satisfies the following rule:

$$I(T) = -\int p(\text{out}) \cdot \ln(p(\text{out})) dt_1^{(1)} \dots dt_{k_1}^{(1)} \dots dt_{k_N}^{(N)} + \\ + \sum_{j=1}^S p_j \int p(\text{out}|s^{(j)}) \cdot \ln(p(\text{out}|s^{(j)})) dt_1^{(1)} \dots dt_{k_1}^{(1)} \dots dt_{k_N}^{(N)}$$

with

$$p(\text{out}) = \sum_{j=1}^S p_j p(\text{out}|s^{(j)}),$$

wherein

- $s^{(j)}$ references an input quantity that is applied to the neural network at a time j ,
- p_j references a probability that the input quantity $s^{(j)}$ is applied to the neural network at a point in time j ,
- $p(\text{out}|s^{(j)})$ references a conditioned probability that a pulse is generated by a pulsed neuron in the neural network under the condition that the input quantity $s^{(j)}$ is applied to the neural network at a point in time j .

6. A method according to claim 1, wherein the training sequence of inputs quantities are is of measured physical signals.

7. A method according to claim 6, wherein the training sequence of input quantities is signals of an electroencephalogram.

8. A method for classification of a sequence of input quantities upon employment of a neural network that contains pulsed neurons and was trained, comprising to the following steps:

- a) training the neural network for a first time span such that a discrimination value is maximized, as a result whereof a maximum first discrimination value is formed;
- b) forming the discrimination value dependent on pulses that are formed by the pulsed neurons within a first time span as well as on a training sequence of input quantities that are supplied to the neural network;
- c) implementing the following steps interactively:
shortening the first time span to form a second time span,
forming a second discrimination value for the second time span,
when the second discrimination value is the same as the first discrimination value, then performing a new iteration with a new second time span that is formed by shortening the second time span of the preceding iteration,
otherwise, ending the method and the trained neural network is the neural network of the last iteration wherein the second discrimination value is the same as the first discrimination value,
supplying the sequence of input quantities to the neural network; and
forming a classification signal that indicates what kind of sequence of input quantities the supplied sequence is.

9. A method according to claim 9, wherein the training sequence of input quantities and the sequence of input quantities are measured physical signals.

10. A method according to claim 9, wherein the training sequence of input quantities and the sequence of input quantities are measured signals of an electroencephalogram.

11. A neural network that contains pulsed neurons has been trained according to the following steps:

- a) the neural network is trained such for a first time span that a discrimination value is maximized, as a result whereof a maximum first discrimination value is formed;
- b) the discrimination value is formed dependent on pulses that are formed by the pulsed neurons within the first time span as well as on a training sequence of input quantities that are supplied to the neural network;
- c) the following steps are interactively implemented:
 - the first time span is shortened to form a second time span,
 - a second discrimination value is formed for the second time span,
 - when the second discrimination value is the same as the first discrimination value, then a new iteration ensues with a new second time span that is formed by shortening the second time span of the preceding iteration,
 - otherwise, the method is ended and the trained neural network is the neural network of the last iteration wherein the second discrimination value is the same as the first discrimination value.

12. A neural network according to claim 10, wherein the network is utilized for classification of a physical signal.

13. A neural network according to claim 10, utilized for the classification of an electroencephalogram signal.

14. An arrangement for training a neural network that contains pulsed neurons comprising:

a processor that is configured such that the following steps implemented:

- a) the neural network is trained such for a first time span that a discrimination value is maximized, as a result whereof a maximum first discrimination value is formed;
- 5 b) the discrimination value is formed dependent on pulses that are formed by the pulsed neurons within the first time span as well as on a training sequence of input quantities that are supplied to the neural network;
- c) the following steps are interactively implemented:
 - the first time span is shortened to form a second time span,
 - 10 a second discrimination value is formed for the second time span, when the second discrimination value is the same as the first discrimination value, then a new iteration ensues with a new second time span that is formed by shortening the second time span of the preceding iteration, and
 - 15 otherwise, the method is ended and the trained neural network is the neural network of the last iteration wherein the second discrimination value is the same as the first discrimination value.

15. An arrangement according to claim 14, wherein the network is utilized for the classification of a physical signal.


20 16. An arrangement according to claim 14, wherein the network is utilized for the classification of a signal of an electroencephalogram.

REMARKS

The foregoing amendments to the specification and claims under Article 41 of the Patent Cooperation Treaty place the application into a form for prosecution before the U.S. Patent and Trademark Office under 35 U.S.C. §371.

5 Accordingly, entry of these amendments before examination on the merits is hereby requested.

Respectfully submitted,



Melvin A. Robinson (reg. no. 31,870)

Schiff Hardin & Waite

Patent Department

6600 Sears Tower

Chicago, Illinois 60606

Telephone: 312-258-5785

10

15

ATTORNEY FOR APPLICANT

CUSTOMER NO. 26574

09763720360
T03660 "03660"

4/PRTS

09/763772
JC02 Rec'd PCT/PTO 26 FEB 2001

Sub Spec.
SPECIFICATION

TITLE

**METHOD FOR TRAINING A NEURAL NETWORK, METHOD FOR
THE CLASSIFICATION OF A SEQUENCE OF INPUT QUANTITIES
UPON EMPLOYMENT OF A NEURAL NETWORK, NEURAL
NETWORK AND ARRANGEMENT FOR THE TRAINING
OF A NEURAL NETWORK**

BACKGROUND OF THE INVENTION

Field of the Invention

10 The present invention is directed to a method for training a neural network, to
a method for the classification of a sequence of input quantities upon employment of a
neural network as well as to a neural network and an arrangement for training a neural
network.

Description of the Related Art

15 A neural network comprises neurons that are at least partially connected to one
another. Input neurons of the neural network are supplied with input signals as input
quantities supplied to the input neurons. The neural network usually comprises a
plurality of layers. A respective neuron generates a signal dependent on input
quantities supplied to a neuron of the neural network and on an activation function
20 provided for the neuron, the signal being in turn supplied to neurons of a further layer
as an input quantity according to a prescribable weighting. An output quantity
dependent on quantities that are supplied to the output neuron of neurons of the
preceding layer is generated in an output neuron in an output layer. There are
currently essentially two approaches in view of the questions as to the form in which
25 information is stored in a neural network.

A first approach assumes that the information in a neural network is encoded
in the spectral domain. Given this approach, a chronological sequence of input
quantities is encoded such that a respective input neuron is provided for each time row
value of a chronological sequence of the input quantities, the respective time row
30 value being applied to this input neuron.

Given a neural network that is designed according to this approach, a hyperbolic tangent (tanh) is usually employed as an activation function.

This first type of neural network is referred to below as a static neural network.

What is particularly disadvantageous about this approach is that it is not
5 possible with a static neural network to explicitly consider a dynamics of a process subject to a technical system in the internal coding of the sequence of input quantities.

The Time Delay Neural Networks (TDNN) known from German Patent Document DE 195 31 697 C2 attempt to counter this disadvantage in that, given a plurality of sequences of input quantities, a respective input neuron is provided for
10 each sequence and for each time row value. This approach particularly exhibits the disadvantage that the dimension of the input space -- represented by the plurality of input neurons -- increases exponentially with an increasing plurality of different sequences of input quantities to be taken into consideration.

An increasing plurality of neurons in the neural network, moreover, involves
15 an increased training outlay upon employment of a plurality of training data that increases with an increasing plurality of neurons. A training of a static neural network becomes highly calculation-intensive under these conditions or, respectively, can practically no longer be implemented.

A gradient-based training method, for example the back-propagation method,
20 is usually utilized for training a static neural network.

The publication by Unnikrishnan, et al., "Alopex: A Correlation-Based Learning Algorithm for Feedforward and Recurrent Neural Networks", also discloses a training method for a static neural network that is referred to as the ALOPEX method. In this method, the training of a static neural network is viewed as an
25 optimization problem. In this case, the goal of the optimization is a minimization of a error criterion E taking weightings that are present in the static neural network and with which the connections between neurons are weighted into consideration for a predetermined training data set with training data.

A training datum is a tuple that has input quantities, for example state quantities of a technical system or, respectively, boundary conditions that a technical system is subject to and that are supplied to a technical system as well as an output quantity determined under the boundary conditions and that the technical system
 5 forms for the input quantities.

The ALOPEX method shall be explained in greater detail later in conjunction with the exemplary embodiment.

A second approach can be seen therein that the information about a system is encoded in the time domain and in the spectral domain. An artificial neural network
 10 that does justice to this approach comprises what are referred to as pulsed neurons and is known from the publication by Gerstner, "Time Structure of the Activity in Neural Networks Models".

According to the publication by Deco et al., "Information Transmission and Temporal Code in Central Spiking Neurons", a pulsed neuron is modelled such that
 15 the behavior of a pulsed neuron with respect to an external stimulation, which is referred to below as an input quantity, is described by a stochastic differential equation of the Itô type according to the following rule:

$$dV(t) = \left(-\frac{V(t)}{\tau} + \mu \right) dt + \sigma dW(t) + w dS(t). \quad (1)$$

In the rule (1), $dW(t)$ references a standard Wiener process. A predetermined constant τ describes a delay of a membrane potential $V(t)$ of the modelled neuron
 20 without an input quantity that is adjacent at the neuron. The model simulates the behavior of a biological neuron. For this reason, a pulsed neuron is also referred to as a biologically oriented neuron.

Further, $S(t)$ references a coupling of the neuron with another neuron, i.e. the following applies:

$$s(t) = \frac{d}{dt} S(t) = \sum_i \delta(t - t_i), \quad (2)$$

whereby t_i references an arrival time at which an external impulse arrives at an input of a neuron. A soma-synaptic intensity is modelled by a synaptic quantity w .

In this model, the pulsed neuron generates a pulse when the membrane potential $V(t)$ reaches a predetermined threshold Θ . After the pulse is generated, the membrane potential $V(t)$ of the neuron is reset to a predetermined initialization potential value $V(0)$.

A time sequence of pulses is thus described according to the following rule:

$$t'_0, \dots, t'_k, \dots, \quad (3)$$

and satisfies the following rule:

$$o(t) = \sum_k \delta(t - t'_k). \quad (4)$$

It is also known from the afore-mentioned Deco et al. publication that, given the assumption of the above-described model for a pulsed neuron, a discrimination value $I(T)$ can be formed that indicates the dependability with which a sequence of input quantities is correctly classified in view of the training data employed for a training of the neural network.

The discrimination value $I(T)$ is dependent on pulses that are formed by the pulsed neurons within a time span $[0; T]$ as well as on a training sequence of input quantities that are supplied to the neural network. The discrimination value $I(T)$ satisfies the following rule:

$$I(T) = I \left[s; \left\{ \begin{matrix} t_1^{(1)}, \dots, t_m^{(1)}, \dots, t_{k_1}^{(1)}, t_1^{(2)}, \dots, t_m^{(2)}, \dots, t_{k_2}^{(2)}, \dots, \\ t_1^{(n)}, \dots, t_m^{(n)}, \dots, t_{k_n}^{(n)}, \dots, t_1^{(N)}, \dots, t_m^{(N)}, \dots, t_{k_N}^{(N)} \end{matrix} \right\} \right], \quad (5)$$

whereby

- s references the input quantities,

- $t_m^{(n)}$ references a pulse that is generated by a pulsed neuron n at a time m within a time span $[0, T]$,
- k_n ($n = 1, \dots, N$) references a point in time at which the pulsed neuron n has generated the last pulse within the time span $[0, T]$,
- 5 • N references a plurality of pulsed neurons contained in the neural network.

A stochastic differential equation of the Itô type derives for a neural network with a plurality of N neurons described according to the following rule:

$$dV_i(t) = \left(-\frac{V_i(t)}{\tau} + \mu \right) dt + \sigma dW_i(t) + \sum_{j=1}^N w_{ij} \sum_k \delta(t - t_{k-\Delta_{ij}}^{(j)}) dt + I_i(t) dt \quad (6)$$

whereby

- $V_i(t)$ references a membrane potential of the i^{th} neuron ($i = 1, \dots, N$),
- 10 • N references a plurality of neurons contained in the neural network,
- w_{ij} respectively references a weighting of a coupling between the i^{th} and the j^{th} neuron, clearly a synaptic intensity between the neurons i and j,
- Δ_{ij} references a prescribable axonal delay of a signal between the neurons i and j,
- 15 • $I_i(t)$ references an external stimulation signal of the neuron i.

The German Patent Document DE 195 31 967C2 discloses a training method for a neural network. Given this method, the neural network is linked in a control circuit with the model of a technical system such that the neural network outputs at least one manipulated variable to the model as an output quantity, and the model
20 generates at least one regulating variable from the manipulated quantity supplied by the neural network, the at least one regulating variable being supplied to the neural network as an input quantity. The regulating variable is superimposed with a noise having a known noise distribution before it is supplied to the model. As a reaction to the regulating variable modified by the impressed noise, the weightings of the neural

network are set as follows: A cost function evaluates whether the change in weighting at the network has effected an improvement of the regulating variable with respect to a rated behavior of the model, and such weightings are favored by the cost function.

SUMMARY OF THE INVENTION

- 5 The present invention is based on providing a method as well as an arrangement for training a neural network having pulsed neurons. The invention is also based on providing a method for the classification of a sequence of input quantities upon employment of a neural network having pulsed neurons as well as specifying a neural network having pulsed neurons.
- 10 The problems are solved by the methods and the arrangement as well as by the neural network trained according to a method for training a neural network that contains pulsed neurons,
- a) the neural network is trained such for a first time span $[0; T]$ that a discrimination value is maximized, as a result whereof a maximum first
 - 15 discrimination value is formed;
 - b) the discrimination value is formed dependent on pulses that are formed by the pulsed neurons within the first time span as well as on a training sequence of input quantities that are supplied to the neural network;
 - c) the following steps are interactively implemented:
 - 20 - the first time span is shortened to form a second time span,
 - a second discrimination value is formed for the second time span,
 - when the second discrimination value is the same as the first discrimination value, then a new iteration ensues with a new second time span that is formed by shortening the second time span of the preceding iteration,
 - 25 - otherwise, the method is ended and the trained neural network is the neural network of the last iteration wherein the second discrimination value is the same as the first discrimination value.

In the preferred method, an optimization method that is not gradient based is utilized for the maximization of the first discrimination value and/or of the second discrimination value. The optimization method may be based on the ALOPEX method.

5 According to one aspect of the invention, the first discrimination value $I(T)$ satisfies the following rule:

$$I(T) = I \left(s; \left\{ \begin{array}{l} t_1^{(1)}, \dots, t_m^{(1)}, \dots, t_{k_1}^{(1)}, t_1^{(2)}, \dots, t_m^{(2)}, \dots, t_{k_2}^{(2)}, \dots, \\ t_1^{(n)}, \dots, t_m^{(n)}, \dots, t_{k_n}^{(n)}, \dots, t_1^{(N)}, \dots, t_m^{(N)}, \dots, t_{k_N}^{(N)} \end{array} \right\} \right),$$

whereby

- s references the input quantities,
 - $t_m^{(n)}$ references a pulse that is generated by a pulsed neuron n at a time m
 - 10 within a time span $[0, T]$,
 - k_n ($n = 1, \dots, N$) references a point in time at which the pulsed neuron n has generated the last pulse within the time span $[0, T]$, and
 - N references a plurality of pulsed neurons contained in the neural network.
- The first discrimination value $I(T)$ in a preferred embodiment satisfies the
- 15 following rule:

$$I(T) = - \int p(\text{out}) \cdot \ln(p(\text{out})) dt_1^{(1)} \dots dt_{k_1}^{(1)} \dots dt_{k_N}^{(N)} + \\ + \sum_{j=1}^S p_j \int p(\text{out} | s^{(j)}) \cdot \ln(p(\text{out} | s^{(j)})) dt_1^{(1)} \dots dt_{k_1}^{(1)} \dots dt_{k_N}^{(N)}$$

with

$$p(\text{out}) = \sum_{j=1}^S p_j p(\text{out} | s^{(j)}),$$

whereby

- $s^{(j)}$ references an input quantity that is applied to the neural network at a time j ,
- p_j references a probability that the input quantity $s^{(j)}$ is applied to the neural network at a point in time j ,
- 5 • $p(\text{out}|s^{(j)})$ references a conditioned probability that a pulse is generated by a pulsed neuron in the neural network under the condition that the input quantity $s^{(j)}$ is applied to the neural network at a point in time j .

According to the foregoing, the training sequence of inputs quantities is measured physical signals, in particular, the training sequence of input quantities is
10 signals of an electroencephalogram.

The present invention provides a method for the classification of a sequence of input quantities upon employment of a neural network that contains pulsed neurons and was trained according to the following steps:

- a) the neural network is trained such for a first time span that a discrimination
15 value is maximized, as a result whereof a maximum first discrimination value is formed;
- b) the discrimination value is formed dependent on pulses that are formed by the pulsed neurons within the first time span as well as on a training sequence of input quantities that are supplied to the neural network;
- 20 c) the following steps are interactively implemented:
 - the first time span is shortened to form a second time span,
 - a second discrimination value is formed for the second time span,
 - when the second discrimination value is the same as the first discrimination value, then a new iteration ensues with a new second time span that is formed
25 by shortening the second time span of the preceding iteration,
 - otherwise, the method is ended and the trained neural network is the neural network of the last iteration wherein the second discrimination value is the same as the first discrimination value,

-- whereby the sequence of input quantities is supplied to the neural network;

- whereby a classification signal is formed that indicates what kind of sequence of input quantities the supplied sequence is.

In the preferred embodiment, the training sequence of input quantities and the sequence of input quantities are measured physical signals, for example, measured signals of an electroencephalogram.

The present invention also provides a neural network that contains pulsed neurons has been trained according to the following steps:

- a) the neural network is trained such for a first time span that a discrimination value is maximized, as a result whereof a maximum first discrimination value is formed;
- b) the discrimination value is formed dependent on pulses that are formed by the pulsed neurons within the first time span as well as on a training sequence of input quantities that are supplied to the neural network;
- c) the following steps are interactively implemented:
 - the first time span is shortened to form a second time span,
 - a second discrimination value is formed for the second time span,
 - when the second discrimination value is the same as the first discrimination value, then a new iteration ensues with a new second time span that is formed by shortening the second time span of the preceding iteration,
 - otherwise, the method is ended and the trained neural network is the neural network of the last iteration wherein the second discrimination value is the same as the first discrimination value.

The neural network is utilized for the classification of a physical signal, such as classification of a signals of an electroencephalogram.

An arrangement for training a neural network that contains pulsed neurons comprises a processor that is configured such that the following steps can be implemented:

- a) the neural network is trained such for a first time span that a discrimination value is maximized, as a result whereof a maximum first discrimination value is formed;
- b) the discrimination value is formed dependent on pulses that are formed by the pulsed neurons within the first time span as well as on a training sequence of input quantities that are supplied to the neural network;
- c) the following steps are interactively implemented:
 - the first time span is shortened to form a second time span,
 - a second discrimination value is formed for the second time span,
 - when the second discrimination value is the same as the first discrimination value, then a new iteration ensues with a new second time span that is formed by shortening the second time span of the preceding iteration,
 - otherwise, the method is ended and the trained neural network is the neural network of the last iteration wherein the second discrimination value is the same as the first discrimination value.

The arrangement may be utilized for the classification of a physical signal, such as for the classification of a signal of an electroencephalogram.

A method for training a neural network that contains pulsed neurons comprises the following steps:

- a) the neural network is trained for a first time span such that a discrimination value is maximized, as a result whereof a maximum first discrimination value is formed;
- b) the discrimination value is formed dependent on pulses that are formed by the pulsed neurons within the first time span as well as on a training sequence of input quantities that are supplied to the neural network;
- c) the following steps are interactively implemented:
 - the first time span is shortened to form a second time span,
 - a second discrimination value is formed for the second time span,

-- when the second discrimination value is the same as the first discrimination value, then a new iteration ensues with a new second time span that is formed by shortening the second time span of the preceding iteration,
 -- otherwise, the method is ended and the trained neural network is the neural network of the last iteration wherein the second discrimination value is the same as the first discrimination value.

A method for the classification of a sequence of input quantities upon employment of a neural network that contains pulsed neurons and was trained according to the following steps comprises the following steps:

- 10 a) the neural network is trained for a first time span such that a discrimination value is maximized, as a result whereof a maximum first discrimination value is formed;
- b) the discrimination value is formed dependent on pulses that are formed by the pulsed neurons within the first time span as well as on a training sequence of input quantities that are supplied to the neural network;
- 15 c) the following steps are interactively implemented:
 - the first time span is shortened to form a second time span,
 - a second discrimination value is formed for the second time span,
 - when the second discrimination value is the same as the first discrimination value, then a new iteration ensues with a new second time span that is formed by shortening the second time span of the preceding iteration,
 - otherwise, the method is ended and the trained neural network is the neural network of the last iteration wherein the second discrimination value is the same as the first discrimination value,
 - 20 -- the sequence of input quantities is supplied to the neural network;
- d) a classification signal is formed that indicates what kind of sequence of input quantities the supplied sequence is.

A neural network that contains pulsed neurons has been trained according to the following steps:

- a) the neural network is trained for a first time span such that a discrimination value is maximized, as a result whereof a maximum first discrimination value is formed;
- b) the discrimination value is formed dependent on pulses that are formed by the pulsed neurons within the first time span as well as on a training sequence of input quantities that are supplied to the neural network;
- c) the following steps are interactively implemented:
 - the first time span is shortened to form a second time span,
 - a second discrimination value is formed for the second time span,
 - when the second discrimination value is the same as the first discrimination value, then a new iteration ensues with a new second time span that is formed by shortening the second time span of the preceding iteration,
 - otherwise, the method is ended and the trained neural network is the neural network of the last iteration wherein the second discrimination value is the same as the first discrimination value.

An arrangement for training a neural network that contains pulsed neurons comprises a processor that is configured such that the following steps can be implemented:

- a) the neural network is trained for a first time span such that a discrimination value is maximized, as a result whereof a maximum first discrimination value is formed;
- b) the discrimination value is formed dependent on pulses that are formed by the pulsed neurons within the first time span as well as on a training sequence of input quantities that are supplied to the neural network;
- c) the following steps are interactively implemented:
 - the first time span is shortened to form a second time span,
 - a second discrimination value is formed for the second time span,

-- when the second discrimination value is the same as the first discrimination value, then a new iteration ensues with a new second time span that is formed by shortening the second time span of the preceding iteration,

5 -- otherwise, the method is ended and the trained neural network is the neural network of the last iteration wherein the second discrimination value is the same as the first discrimination value.

The invention makes it possible to classify a time sequence of input quantities with a neural network what contains pulsed neurons, whereby it is assured that, given optimized classification dependability, a minimized plurality of time values must be
10 supplied to the neural network for classification.

Preferred developments of the invention INSERT DEPENDENT CLAIMS.

An optimization method that is not gradient based is preferably employed for the maximization of the first discrimination value and/or the second discrimination value, preferably an optimization method based on the ALOPEX method.

15 The first discrimination value preferably satisfies the following rule:

$$I(T) = I \left[s; \left\{ \begin{array}{l} t_1^{(1)}, \dots, t_m^{(1)}, \dots, t_{k_1}^{(1)}, t_1^{(2)}, \dots, t_m^{(2)}, \dots, t_{k_2}^{(2)}, \dots, \\ t_1^{(n)}, \dots, t_m^{(n)}, \dots, t_{k_n}^{(n)}, \dots, t_1^{(N)}, \dots, t_m^{(N)}, \dots, t_{k_N}^{(N)} \end{array} \right\} \right], \quad (7)$$

whereby

- s references the input quantities,
- $t_m^{(n)}$ references a pulse that is generated by a pulsed neuron n at a time m within a time span [0, T],
- 20 • k_n ($n = 1, \dots, N$) references a point in time at which the pulsed neuron n has generated the last pulse within the time span [0, T],
- N references a plurality of pulsed neurons contained in the neural network.

In a further development, the first discrimination value satisfies the following rule:

$$\begin{aligned}
I(T) = & -\int p(\text{out}) \cdot \ln(p(\text{out})) dt_1^{(1)} \dots dt_{k_1}^{(1)} \dots dt_{k_N}^{(N)} + \\
& + \sum_{j=1}^S p_j \int p(\text{out}|s^{(j)}) \cdot \ln(p(\text{out}|s^{(j)})) dt_1^{(1)} \dots dt_{k_1}^{(1)} \dots dt_{k_N}^{(N)} \quad (8)
\end{aligned}$$

with

$$p(\text{out}) = \sum_{j=1}^S p_j p(\text{out}|s^{(j)}), \quad (9)$$

whereby

- $s^{(j)}$ references an input quantity that is applied to the neural network at a time j ,
- p_j references a probability that the input quantity $s^{(j)}$ is applied to the neural network at a point in time j ,
- $p(\text{out}|s^{(j)})$ references a conditioned probability that a pulse is generated by a pulsed neuron in the neural network under the condition that the input quantity $s^{(j)}$ is applied to the neural network at a point in time j .

The training sequences of input quantities are preferably measured physical signals.

The methods and the arrangements can thus be utilized in the framework of the description of a technical system, particularly for describing or, respectively, investigating a multi-channel signal that has been registered by an electroencephalograph and describes an electroencephalogram.

The methods and the arrangements can also be utilized for the analysis of multi-variant financial data in a financial market for the analysis of economic relationships.

The described method steps can be realized both in software for the processor as well as in hardware, i.e. with a specific circuit.

BRIEF DESCRIPTION OF DRAWINGS

An exemplary embodiment of the invention is shown in the Figures and is explained in greater detail below.

- Figure 1 is a flowchart wherein the individual method steps of the exemplary embodiment are presented;
- Figure 2 is a functional block diagram showing an electroencephalograph and a patient for whom a electroencephalogram is produced;
- Figure 3 is a schematic diagram of a neural network according to the exemplary embodiment;
- Figure 4 is a schematic diagram on the basis whereof the principle underlying the exemplary embodiment is shown.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

- Figure 2** shows a patient 200 to whose head 201 sensors 202, 203, 204, 205 and 206 are attached for the registration of brain currents. Electrical signals 207, 208, 209, 210 and 211 picked up by the sensors 202, 203, 204, 205, 206 are supplied to an electroencephalograph 220 via a first input/output interface 221. The electroencephalograph 220 comprises a plurality of input channels. Via the input/output interface 221, which is connected to an analog-to-digital converter 222, the electrical signals are supplied to the electroencephalograph 220 and digitalized in the analog-to-digital converter 222, and each registered electrical signal is stored in a memory 223 as a sequence of time row values.

- A sequence of time row values is thus characterized by a sampling interval as well as by a time duration, referred to below as a time span, during which a respective electrical signal is registered. The memory 223 is connected to the analog-to-digital converter 222 as well as to a processor 224 and a second input-output interface 225 via a bus 226.

A picture screen 228 (via a first cable 227), a keyboard 230 (via a second cable 229) and a computer mouse 232 (via a third cable) are also connected to the second input/output interface 225.

Results of the examination of the patient 200 are shown on the picture screen 228. A user (not shown) can make inputs into the system via the keyboard 230 or, respectively, the computer mouse 232.

The processor 224 is configured such that the method steps described later can be implemented.

A respective sequence of time row values as well as particular information about the class of time row values to which the sequence of time row values is to be allocated form a training datum.

A plurality of training data form a training data set with which a neural network 301 described later is trained.

Figure 3 shows the neural network 301 with pulsed neurons.

A sequence 306, 307 and 308 of time row values is respectively applied to a respective input neuron 302, 303 and 304 of an input layer 305. A particular information as to whether the sequence 306, 307 and 308 of the time row values, broadly referred to as input pattern 306, 307 and 308, is a matter of an input pattern 306, 307 and 308 of a first class or a matter of an input pattern 306, 307 and 308 of a second class is allocated to each applied sequence 306, 307 and 308 of time row values in the framework of the training method.

A respective input neuron 302, 303 and 304 is respectively connected to an intermediate neuron 309, 310 and 311 of an intermediate layer 312 via a weighted connection 313, 314 and 315.

The intermediate neurons 309, 310 and 311 are connected to one another via connections 316, 317, 318, 319, 320 and 321 that are likewise weighted.

The intermediate neurons 309, 310 and 311 are also connected to further pulsed neurons 322, 323 and 324 via weighted connections 325, 326, 327, 328, 329 and 330.

The pulsed neurons respectively comprise the above-described behavior that is presented in the publication by Gerstner, "Time Structure of the Activity in Neural Network Models".

The intermediate neurons 309, 310 and 311 are connected to a plurality of the intermediate neurons 309, 310 and 311; the respective, further pulsed neurons 322, 323 and 324 are respectively connected to exactly one intermediate neuron 309, 310, 311. In this way, it is possible to model a far-reaching influencing between neurons of a neural network as well as a local influencing of neurons within the neural network.

An output neuron 331 is connected to the further pulsed neurons 322, 323 and 324 via weighted connections 332, 333 and 334. The output neuron 331 forms an output signal 335 that indicates the class to which the input pattern 306, 307 and 308 belongs.

In the training phase of the neural network 301, the output quantity 335 is compared to the classification particular information allocated to the respective input pattern, and an error signal E is formed that is employed for adapting the weightings of the connections between the neurons present in the neural network 301.

The method according to the ALOPEX method, which is not gradient based, is utilized as the training method in the framework of this exemplary embodiment. The goal of the ALOPEX method is the minimization of an error criterion E taking into consideration and adapting the weightings w_{bc} for a training dataset.

The ALOPEX is explained in greater detail below.

A neuron b is connected to a neuron c via a connection that is weighted with the weighting w_{bc} . During an f^{th} iteration, the weighting w_{bc} is updated according to the following rule:

$$w_{bc}(f) = w_{bc}(f - 1) + \delta_{bc}(f), \quad (10)$$

whereby $\delta_{bc}(f)$ references a small positive or negative, predetermined step width δ according to the following rule:

$$\delta_{bc}(f) = \begin{cases} -\delta & \text{with a probability } p_{bc}(f) \\ +\delta & \text{with a probability } 1 - p_{bc}(f) \end{cases} \quad (11)$$

A probability $p_{bc}(f)$ is formed according to the following rule:

$$p_{bc}(f) = \frac{1}{1 + e^{-\frac{C_{bc}(f)}{T(f)}}} \quad (12)$$

whereby $C_{bc}(f)$ is formed according to the following rule:

$$C_{bc}(f) = \Delta w_{bc}(f) \cdot \Delta E(f) \quad (13)$$

$T(f)$ references a prescribable value. $\Delta w_{bc}(f)$ and $\Delta E(f)$ reference the weighting changes $\Delta w_{bc}(f)$ of the weightings w_{bc} or, respectively, the change $\Delta E(f)$ of the error criterion during the preceding two iterations according to the rules:

$$\Delta w_{bc}(f) = w_{bc}(f-1) - w_{bc}(f-2) \quad (14)$$

$$\Delta E_{bc}(f) = E_{bc}(f-1) - E_{bc}(f-2) \quad (15)$$

The predetermined value $T(f)$ is updated every F iterations according to the following rule:

$$T(f) = \frac{1}{FM} \sum_b \sum_c \sum_{f'=f-F}^{f-1} |C_{bc}(f')| \quad (16)$$

when f is a whole multiple of F , and

$$T(f) = T(f-1) \quad \text{otherwise,} \quad (17)$$

whereby M references a plurality of connections in the neural network 301.

Equation (16) can be simplified to form the following rule:

$$T(\mathbf{f}) = \frac{\delta}{F} \sum_{\mathbf{f}' = \mathbf{f} - \mathbf{F}}^{\mathbf{f} - 1} |\Delta E(\mathbf{f}')|. \quad (18)$$

The neural network 301 is trained according to the above-described training method upon employment of the training dataset.

Further, a first discrimination value $I(T)$ for the neural network 301 is formed according to the following rule:

$$I(T) = I \left(s; \left\{ \begin{array}{l} t_1^{(1)}, \dots, t_m^{(1)}, \dots, t_{k_1}^{(1)}, t_1^{(2)}, \dots, t_m^{(2)}, \dots, t_{k_2}^{(2)}, \dots, \\ t_1^{(n)}, \dots, t_m^{(n)}, \dots, t_{k_n}^{(n)}, \dots, t_1^{(N)}, \dots, t_m^{(N)}, \dots, t_{k_N}^{(N)} \end{array} \right\} \right), \quad (19)$$

5 whereby

- s references the input quantities,
- $t_m^{(n)}$ references a pulse that is generated by a pulsed neuron n at a time m within a time span $[0, T]$,
- k_n ($n = 1, \dots, N$) references a point in time at which the pulsed neuron n has generated the last pulse within the time span $[0, T]$,
- N references a plurality of pulsed neurons contained in the neural network.

10

The first discrimination value $I(T)$ clearly corresponds to the difference of the following entropies:

$$I(T) = H(\text{out}) - \langle H(\text{out}|s) \rangle_s, \quad (20)$$

with

$$H(\text{out}) = - \int p(\text{out}) \cdot \ln(p(\text{out})) dt_1^{(1)} \dots dt_{k_1}^{(1)} \dots dt_{k_N}^{(N)} \quad (21)$$

and

$$\langle H(\text{out}|s) \rangle_s = - \sum_{j=1}^S p_j \int p(\text{out}|s^{(j)}) \cdot \ln(p(\text{out}|s^{(j)})) dt_1^{(1)} \dots dt_{k_1}^{(1)} \dots dt_{k_N}^{(N)}. \quad (22)$$

The first discrimination value $I(T)$ thus derives according to the following rule:

whereby

- $s^{(j)}$ references an input quantity that is applied to the neural network at a time j ,
- p_j references a probability that the input quantity $s^{(j)}$ is applied to the neural network at a point in time j ,
- $p(\text{out}|s^{(j)})$ references a conditioned probability that a pulse is generated by a pulsed neuron in the neural network under the condition that the input quantity $s^{(j)}$ is applied to the neural network at a point in time j .

When a maximum first discrimination value $I(T)$ has been determined in the framework of training the neural network 301, then this means that the input pattern 306, 307, 308 observed in the first time span contains enough information in order to classify the input pattern with adequate dependability.

The first discrimination value $I(T)$ is clearly formed (step 101) in the framework of the training for a first time span $[0; T]$ (see **Figure 1**).

In a further step (step 102), a second time span is formed by shortening the first time span: $[0; T']$, whereby $T' < T$ applies.

For the second time span $[0; T']$, a second discrimination value $I(T')$ is formed in a further step (step 103) in the same way as described above for the first
5 discrimination value $I(T)$.

The first discrimination value $I(T)$ is compared to the second discrimination value $I(T')$ (step 104).

When the second discrimination value $I(T')$ is the same as the first discrimination value $I(T)$, then a new second time span is formed (step 105) by
10 shortening the second time span $[0; T']$, and the new second time span is considered to be the second time span (step 106). A second discrimination value $I(T')$ is in turn formed (step 103) for the second time span of the new iteration.

Clearly, this iterative method means that the time span wherein pulses generated by the pulsed neurons are taken into consideration for forming the output
15 signal is shortened until the second discrimination value $I(T')$ is unequal to the first discrimination value $I(T)$.

When the second discrimination value $I(T')$ is smaller than the first discrimination value, then the neural network 301 is viewed as being an optimized neural network that was trained in the last preceding iteration wherein the second
20 discrimination value $I(T')$ was not smaller than the first discrimination value $I(T)$ (step 107).

The time span respectively taken into consideration is divided into discrete time sub-spans for which the only thing respectively determined is whether a neuron generated a pulse during the time sub-span or not.

25 In this way, the calculating outlay needed for the training is considerably reduced.

For further illustration, the principle is explained again on the basis of **Figure 4**.

Figure 4 shows two continuous processes p1 and p2 that are formed by a set of continuous input signals S1 and S2. Two sequences of input quantities, the input patterns, are present after a corresponding, above-described digitalization. The input patterns are supplied to the trained neural network 401 in an application phase, and a
5 space-time encoding of the processes p1 and p2 is clearly implemented on the basis of the time rows for the trained neural network 401.

On the basis of an output signal 402, the trained neural network 401 indicates the kind of process the input pattern involves. The trained neural network 401 exhibits the property that, first, the dependability of the optimization is optimized and,
10 second, a minimum plurality of time row values, i.e. a minimum second time span 403, is required in order to dependably implement the classification.

A few alternatives to the above-described exemplary embodiment are present below:

The plurality of inputs, of pulsed neurons as well as output signals is generally
15 arbitrary. The plurality of different sequences of time row values is also arbitrary in the framework of the classification and in the framework of the training. An electroencephalogram analysis is thus possible for an arbitrary plurality of channels for characterizing tumors.

Although other modifications and changes may be suggested by those skilled
20 in the art, it is the intention of the inventors to embody within the patent warranted hereon all changes and modifications as reasonably and properly come within the scope of their contribution to the art.

**METHOD FOR TRAINING A NEURAL NETWORK, METHOD FOR THE
CLASSIFICATION OF A SEQUENCE OF INPUT QUANTITIES UPON
EMPLOYMENT OF A NEURAL NETWORK, NEURAL NETWORK AND
ARRANGEMENT FOR THE TRAINING OF A NEURAL NETWORK**

5 The invention is directed to a method for training a neural network, to a method for the classification of a sequence of input quantities upon employment of a neural network as well as to a neural network and an arrangement for training a neural network.

10 A neural network comprises neurons that are at least partially connected to one another. Input neurons of the neural network are supplied with input signals as input quantities supplied to the input neurons. The neural network usually comprises a plurality of layers. A respective neuron generates a signal dependent on input quantities supplied to a neuron of the neural network and on an activation function provided for the neuron, said signal being in turn supplied to neurons of a further
15 layer as input quantity according to a prescribable weighting. An output quantity dependent on quantities that are supplied to the output neuron of neurons of the preceding layer is generated in an output neuron in an output layer. There are currently essentially two approaches in view of the questions as to the form in which information is stored in a neural network.

20 A first approach assumes that the information in a neural network is encoded in the spectral domain. Given this approach, a chronological sequence of input quantities is encoded such that a respective input neuron is provided for each time row value of a chronological sequence of the input quantities, the respective time row value being applied to this input neuron.

25 Given a neural network that is designed according to this approach, a hyperbolic tangent (tanh) is usually employed as activation function.

 This first type of neural network is referred to below as static neural network.

What is particularly disadvantageous about this approach is that it is not possible with a static neural network to explicitly consider a dynamics of a process subject to a technical system in the internal coding of the sequence of input quantities.

The Time Delay Neural Networks (TDNN) known from [4] attempt to
 5 counter this disadvantage in that, given a plurality of sequences of input quantities, a respective input neuron is provided for each sequence and for each time row value. This approach particularly exhibits the disadvantage that the dimension of the input space -- represented by the plurality of input neurons -- increases exponentially with an increasing plurality of different sequences of input quantities to be taken into
 10 consideration.

An increasing plurality of neurons in the neural network, moreover, involves an increased training outlay upon employment of a plurality of training data that increases with an increasing plurality of neurons. A training of a static neural network becomes highly calculation-intensive under these conditions or, respectively,
 15 can practically no longer be implemented.

A gradient-based training method, for example the back-propagation method, is usually utilized for training a static neural network.

[3] also discloses a training method for a static neural network that is referred to as the ALOPEX method. In this method, the training of a static neural
 20 network is viewed as an optimization problem. In this case, the goal of the optimization is a minimization of a error criterion E taking weightings that are present in the static neural network and with which the connections between neurons are weighted into consideration for a predetermined training data set with training data.

A training datum is a tuple that [...] input quantities, for example state
 25 quantities of a technical system or, respectively, boundary conditions that a technical system is subject to and that are supplied to a technical system as well as an output quantity determined under the boundary conditions and that the technical system forms for the input quantities.

The ALOPEX method shall be explained in greater detail later in
 30 conjunction with the exemplary embodiment.

A second approach can be seen therein that the information about a system is encoded in the time domain and in the spectral domain. An artificial neural network that does justice to this approach comprises what are referred to as pulsed neurons and is known from [2].

- 5 According to [1], a pulsed neuron is modelled such that the behavior of a pulsed neuron with respect to an external stimulation, which is referred to below as input quantity, is described by a stochastic differential equation of the Itô type according to the following rule:

$$dV(t) = \left(-\frac{V(t)}{\tau} + \mu \right) dt + \sigma dW(t) + w dS(t). \quad (1)$$

- 10 In the rule (1), $dW(t)$ references a standard Wiener process. A predetermined constant τ describes a delay of a membrane potential $V(t)$ of the modelled neuron without input quantity that is adjacent at the neuron. The model simulates the behavior of a biological neuron. For this reason, a pulsed neuron is also referred to as biologically oriented neuron.

- 15 Further, $S(t)$ references a coupling of the neuron with another neuron, i.e. the following applies:

$$s(t) = \frac{d}{dt} S(t) = \sum_i \delta(t - t_i), \quad (2)$$

whereby t_i references an arrival time at which an external impulse arrives at an input of a neuron. A soma-synaptic intensity is modelled by a synaptic quantity w .

- 20 In this model, the pulsed neuron generates a pulse when the membrane potential $V(t)$ reaches a predetermined threshold Θ . After the pulse is generated, the membrane potential $V(t)$ of the neuron is reset to a predetermined initialization potential value $V(0)$.

A time sequence of pulses is thus described according to the following rule:

$$t'_0, \dots, t'_k, \dots, \quad (3)$$

and satisfies the following rule:

$$o(t) = \sum_k \delta(t - t_k'). \quad (4)$$

It is also known from [1] that, given the assumption of the above-described model for a pulsed neuron, a discrimination value $I(T)$ can be formed that indicates the dependability with which a sequence of input quantities is correctly classified in view of the training data employed for a training of the neural network.

The discrimination value $I(T)$ is dependent on pulses that are formed by the pulsed neurons within a time span $[0; T]$ as well as on a training sequence of input quantities that are supplied to the neural network. The discrimination value $I(T)$ satisfies the following rule:

$$I(T) = I \left[s; \left\{ t_1^{(1)}, \dots, t_m^{(1)}, \dots, t_{k_1}^{(1)}, t_1^{(2)}, \dots, t_m^{(2)}, \dots, t_{k_2}^{(2)}, \dots, \right. \right. \\ \left. \left. t_1^{(n)}, \dots, t_m^{(n)}, \dots, t_{k_n}^{(n)}, \dots, t_1^{(N)}, \dots, t_m^{(N)}, \dots, t_{k_N}^{(N)} \right\} \right], \quad (5)$$

whereby

- s references the input quantities,
- $t_m^{(n)}$ references a pulse that is generated by a pulsed neuron n at a time m within a time span $[0, T]$,
- k_n ($n = 1, \dots, N$) references a point in time at which the pulsed neuron n has generated the last pulse within the time span $[0, T]$,
- N references a plurality of pulsed neurons contained in the neural network.

A stochastic differential equation of the Itô type derives for a neural network with a plurality of N neurons described according to the following rule:

$$dV_i(t) = \left(-\frac{V_i(t)}{\tau} + \mu \right) dt + \sigma dW_i(t) + \\ + \sum_{j=1}^N w_{ij} \sum_k \delta(t - t_{k-\Delta_{ij}}^{(j)}) dt + I_i(t) dt, \quad (6)$$

whereby

- $V_i(t)$ references a membrane potential of the i^{th} neuron ($i = 1, \dots, N$),
 - N references a plurality of neurons contained in the neural network,
 - w_{ij} respectively references a weighting of a coupling between the i^{th} and the j^{th} neuron, clearly a synaptic intensity between the neurons i and j ,
 - Δ_{ij} references a prescribable axonal delay of a signal between the neurons i and j ,
 - $I_i(t)$ references an external stimulation signal of the neuron i .
- [4] discloses a training method for a neural network. Given this method,
- the neural network is linked such in a control circuit with the model of a technical system that the neural network outputs at least one manipulated variable to the model as output quantity, and the model generates at least one regulating variable from the manipulated quantity supplied by the neural network, said at least one regulating variable being supplied to the neural network as input quantity. The regulating variable is superimposed with a noise having a known noise distribution before it is supplied to the model. As a reaction to the regulating variable modified by the impressed noise, the weightings of the neural network are set as follows: A cost function evaluates whether the change in weighting at the network has effected an improvement of the regulating variable with respect to a rated behavior of the model, and such weightings are favored by the cost function.

The invention is based on the problem of specifying a method as well as an arrangement for training a neural network having pulsed neurons. The invention is also based on the problem of specifying a method for the classification of a sequence of input quantities upon employment of a neural network having pulsed neurons as well as specifying a neural network having pulsed neurons.

The problems are solved by the methods and the arrangement as well as by the neural network having the features of the independent patent claims.

A method for training a neural network that contains pulsed neurons comprises the following steps:

- a) the neural network is trained such for a first time span that a discrimination value is maximized, as a result whereof a maximum first discrimination value is formed;
- b) the discrimination value is formed dependent on pulses that are formed by the pulsed neurons within the first time span as well as on a training sequence of input quantities that are supplied to the neural network;
- c) the following steps are interactively implemented:
 - the first time span is shortened to form a second time span,
 - a second discrimination value is formed for the second time span,
 - when the second discrimination value is the same as the first discrimination value, then a new iteration ensues with a new second time span that is formed by shortening the second time span of the preceding iteration,
 - otherwise, the method is ended and the trained neural network is the neural network of the last iteration wherein the second discrimination value is the same as the first discrimination value.

A method for the classification of a sequence of input quantities upon employment of a neural network that contains pulsed neurons and was trained according to the following steps comprises the following steps:

- a) the neural network is trained such for a first time span that a discrimination value is maximized, as a result whereof a maximum first discrimination value is formed;
- b) the discrimination value is formed dependent on pulses that are formed by the pulsed neurons within the first time span as well as on a training sequence of input quantities that are supplied to the neural network;
- c) the following steps are interactively implemented:
 - the first time span is shortened to form a second time span,
 - a second discrimination value is formed for the second time span,
 - when the second discrimination value is the same as the first discrimination value, then a new iteration ensues with a new second time

span that is formed by shortening the second time span of the preceding iteration,

-- otherwise, the method is ended and the trained neural network is the neural network of the last iteration wherein the second discrimination value is the same as the first discrimination value,

-- the sequence of input quantities is supplied to the neural network;

d) a classification signal is formed that indicates what kind of sequence of input quantities the supplied sequence is.

A neural network that contains pulsed neurons has been trained according

to the following steps:

a) the neural network is trained such for a first time span that a discrimination value is maximized, as a result whereof a maximum first discrimination value is formed;

b) the discrimination value is formed dependent on pulses that are formed by the pulsed neurons within the first time span as well as on a training sequence of input quantities that are supplied to the neural network;

c) the following steps are interactively implemented:

-- the first time span is shortened to form a second time span,

-- a second discrimination value is formed for the second time span,

-- when the second discrimination value is the same as the first discrimination value, then a new iteration ensues with a new second time span that is formed by shortening the second time span of the preceding iteration,

-- otherwise, the method is ended and the trained neural network is the neural network of the last iteration wherein the second discrimination value is the same as the first discrimination value.

An arrangement for training a neural network that contains pulsed neurons comprises a processor that is configured such that the following steps can be implemented:

- a) the neural network is trained such for a first time span that a discrimination value is maximized, as a result whereof a maximum first discrimination value is formed;
- b) the discrimination value is formed dependent on pulses that are formed by the pulsed neurons within the first time span as well as on a training sequence of input quantities that are supplied to the neural network;
- c) the following steps are interactively implemented:
- the first time span is shortened to form a second time span,
 - a second discrimination value is formed for the second time span,
 - when the second discrimination value is the same as the first discrimination value, then a new iteration ensues with a new second time span that is formed by shortening the second time span of the preceding iteration,
 - otherwise, the method is ended and the trained neural network is the neural network of the last iteration wherein the second discrimination value is the same as the first discrimination value.

The invention makes it possible to classify a time sequence of input quantities with a neural network what contains pulsed neurons, whereby it is assured that, given optimized classification dependability, a minimized plurality of time values must be supplied to the neural network for classification.

Preferred developments of the invention derive from the dependent claims.

An optimization method that is not gradient based is preferably employed for the maximization of the first discrimination value and/or the second discrimination value, preferably an optimization method based on the ALOPEX method.

The first discrimination value preferably satisfies the following rule:

$$I(T) = I \left(s, \left\{ \begin{matrix} t_1^{(1)}, \dots, t_m^{(1)}, \dots, t_{k_1}^{(1)}, t_1^{(2)}, \dots, t_m^{(2)}, \dots, t_{k_2}^{(2)}, \dots, \\ t_1^{(n)}, \dots, t_m^{(n)}, \dots, t_{k_n}^{(n)}, \dots, t_1^{(N)}, \dots, t_m^{(N)}, \dots, t_{k_N}^{(N)} \end{matrix} \right\} \right), \quad (7)$$

whereby

- s references the input quantities,

- $t_m^{(n)}$ references a pulse that is generated by a pulsed neuron n at a time m within a time span $[0, T]$,
 - k_n ($n = 1, \dots, N$) references a point in time at which the pulsed neuron n has generated the last pulse within the time span $[0, T]$,
 - 5 • N references a plurality of pulsed neurons contained in the neural network.
- In a further development, the first discrimination value satisfies the

following rule:

$$I(T) = -\int p(\text{out}) \cdot \ln(p(\text{out})) dt_1^{(1)} \dots dt_{k_1}^{(1)} \dots dt_{k_N}^{(N)} + \\ + \sum_{j=1}^S p_j \int p(\text{out}|s^{(j)}) \cdot \ln(p(\text{out}|s^{(j)})) dt_1^{(1)} \dots dt_{k_1}^{(1)} \dots dt_{k_N}^{(N)} \quad (8)$$

with

$$p(\text{out}) = \sum_{j=1}^S p_j p(\text{out}|s^{(j)}), \quad (9)$$

whereby

- $s^{(j)}$ references an input quantity that is applied to the neural network at a time j ,
- 10 • p_j references a probability that the input quantity $s^{(j)}$ is applied to the neural network at a point in time j ,
- $p(\text{out}|s^{(j)})$ references a conditioned probability that a pulse is generated by a pulsed neuron in the neural network under the condition that the input quantity $s^{(j)}$ is applied to the neural network at a point in time j .
- 15

The training sequences of input quantities are preferably measured physical signals.

The methods and the arrangements can thus be utilized in the framework of the description of a technical system, particularly for describing or, respectively,

20 investigating a multi-channel signal that has been registered by an electroencephalograph and describes an electroencephalogram.

The methods and the arrangements can also be utilized for the analysis of multi-variant financial data in a financial market for the analysis of economic relationships.

5 The described method steps can be realized both in software for the processor as well as in hardware, i.e. with a specific circuit.

An exemplary embodiment of the invention is shown in the Figures and is explained in greater detail below.

Shown are:

- 10 Figure 1 a flowchart wherein the individual method steps of the exemplary embodiment are presented;
- Figure 2 a sketch of an electroencephalograph and a patient for whom a electroencephalogram is produced;
- Figure 3 a sketch of a neural network according to the exemplary embodiment;
- 15 Figure 4 a sketch on the basis whereof the principle underlying the exemplary embodiment is shown.

Figure 2 shows a patient 200 to whose head 201 sensors 202, 203, 204, 205 and 206 are attached for the registration of brain stomata [sic; should probably read "currents"]. Electrical signals 207, 208, 209, 210 and 211 picked up by the sensors 202, 203, 204, 205, 206 are supplied to an electroencephalograph 220 via a
20 first input/output interface 221. The electroencephalograph 220 comprises a plurality of input channels. Via the input/output interface 221, which is connected to an analog-to-digital converter 222, the electrical signals are supplied to the electroencephalograph 220 and digitalized in the analog-to-digital converter 222, and each registered electrical signal is stored in a memory 223 as a sequence or time row
25 values.

A sequence of time row values is thus characterized by a sampling interval as well as by a time duration, referred to below as time span, during which a respective electrical signal is registered. The memory 223 is connected to the analog-to-digital converter 222 as well as to a processor 224 and a second input-output
30 interface 225 via a bus 226.

A picture screen 228 (via a first cable 227), a keyboard 230 (via a second cable 229) and a computer mouse 232 (via a third cable) are also connected to the second input/output interface 225.

Results of the examination of the patient 200 are shown on the picture screen 228. A user (not shown) can make inputs into the system via the keyboard 230 or, respectively, the computer mouse 232.

The processor 224 is configured such that the method steps described later can be implemented.

A respective sequence of time row values as well as a particular about the class of time row values to which the sequence of time row values is to be allocated form a training datum.

A plurality of training data form a training data set with which a neural network 301 described later is trained.

Figure 3 shows the neural network 301 with pulsed neurons.

A sequence 306, 307, 308 of time row values is respectively applied to a respective input neuron 302, 303, 304 of an input layer 305. A particular as to whether the sequence 306, 307, 308 of the time row values, broadly referred to as input pattern 306, 307, 308, is a matter of an input pattern 306, 307, 308 of a first class or a matter of an input pattern 306, 307, 308 of a second class is allocated to each applied sequence 306, 307, 308 of time row values in the framework of the training method.

A respective input neuron 302, 303, 304 is respectively connected to an intermediate neuron 309, 310, 311 of an intermediate layer 312 via a weighted connection 313, 314, 315.

The intermediate neurons 309, 310, 311 are connected to one another via connections 316, 317, 318, 319, 320, 321 that are likewise weighted.

The intermediate neurons 309, 310, 311 are also connected to further pulsed neurons 322, 323, 324 via weighted connections 325, 326, 327, 328, 329 and 330.

The pulsed neurons respectively comprise the above-described behavior that is presented in [2].

The intermediate neurons 309, 310, 311 are connected to a plurality of intermediate neurons 309, 310, 311; the respective, further pulsed neurons 322, 323, 324 are respectively connected to exactly one intermediate neuron 309, 310, 311. In this way, it is possible to model a far-reaching influencing between neurons of a neural network as well as a local influencing of neurons within the neural network.

An output neuron 331 is connected to the further pulsed neurons 322, 323, 324 via weighted connections 332, 333 and 334. The output neuron 331 forms an output signal 335 that indicates the class to which the input pattern 306, 307, 308 belongs.

In the training phase of the neural network 301, the output quantity 335 is compared to the classification particular allocated to the respective input pattern, and an error signal E is formed that is employed for adapting the weightings of the connections between the neurons present in the neural network 301.

The method according to the ALOPEX method, which is not gradient based, is utilized as the training method in the framework of this exemplary embodiment. The goal of the ALOPEX method is the minimization of an error criterion E taking into consideration and adapting the weightings w_{bc} for a training dataset.

The ALOPEX is explained in greater detail below.

A neuron b is connected to a neuron c via a connection that is weighted with the weighting w_{bc} . During an f^{th} iteration, the weighting w_{bc} is updated according to the following rule:

$$w_{bc}(f) = w_{bc}(f - 1) + \delta_{bc}(f), \quad (10)$$

whereby $\delta_{bc}(f)$ references a small positive or negative, predetermined step width δ according to the following rule:

$$\delta_{bc}(f) = \begin{cases} -\delta & \text{with a probability } p_{bc}(f) \\ +\delta & \text{with a probability } 1 - p_{bc}(f) \end{cases}. \quad (11)$$

A probability $p_{bc}(f)$ is formed according to the following rule:

$$p_{bc}(f) = \frac{1}{1 + e^{-\frac{C_{bc}(f)}{T(f)}}}, \quad (12)$$

whereby $C_{bc}(f)$ is formed according to the following rule:

$$C_{bc}(f) = \Delta w_{bc}(f) \cdot \Delta E(f). \quad (13)$$

$T(f)$ references a prescribable value. $\Delta w_{bc}(f)$ and $\Delta E(f)$ reference the weighting changes $\Delta w_{bc}(f)$ of the weightings w_{bc} or, respectively, the change $\Delta E(f)$ of the error criterion during the preceding two iterations according to the rules:

$$\Delta w_{bc}(f) = w_{bc}(f-1) + w_{bc}(f-2), \quad (14)$$

$$\Delta E_{bc}(f) = E_{bc}(f-1) + E_{bc}(f-2). \quad (15)$$

The predetermined value $T(f)$ is updated every F iterations according to the following rule:

$$T(f) = \frac{1}{FM} \sum_b \sum_c \sum_{f'=f-F}^{f-1} |C_{bc}(f')| \quad (16)$$

when f is a whole multiple of F , and

$$T(f) = T(f-1) \quad \text{otherwise}, \quad (17)$$

whereby M references a plurality of connections in the neural network 301.

Equation (16) can be simplified to form the following rule:

$$T(f) = \frac{\delta}{F} \sum_{f'=f-F}^{f-1} |\Delta E(f')|. \quad (18)$$

The neural network 301 is trained according to the above-described training method upon employment of the training dataset.

Further, a first discrimination value $I(T)$ for the neural network 301 is formed according to the following rule:

$$I(T) = I \left[s; \left\{ \begin{array}{l} t_1^{(1)}, \dots, t_m^{(1)}, \dots, t_{k_1}^{(1)}, t_1^{(2)}, \dots, t_m^{(2)}, \dots, t_{k_2}^{(2)}, \dots, \\ t_1^{(n)}, \dots, t_m^{(n)}, \dots, t_{k_n}^{(n)}, \dots, t_1^{(N)}, \dots, t_m^{(N)}, \dots, t_{k_N}^{(N)} \end{array} \right\} \right], \quad (19)$$

whereby

- s references the input quantities,
- 5 • $t_m^{(n)}$ references a pulse that is generated by a pulsed neuron n at a time m within a time span $[0, T]$,
- k_n ($n = 1, \dots, N$) references a point in time at which the pulsed neuron n has generated the last pulse within the time span $[0, T]$,
- N references a plurality of pulsed neurons contained in the neural network.

10 The first discrimination value $I(T)$ clearly corresponds to the difference of the following entropies:

$$I(T) = H(\text{out}) - \langle H(\text{out}|s) \rangle_s, \quad (20)$$

with

$$H(\text{out}) = - \int p(\text{out}) \cdot \ln(p(\text{out})) dt_1^{(1)} \dots dt_{k_1}^{(1)} \dots dt_{k_N}^{(N)} \quad (21)$$

and

$$\langle H(\text{out}|s) \rangle_s = - \sum_{j=1}^s p_j \int p(\text{out}|s^{(j)}) \cdot \ln(p(\text{out}|s^{(j)})) dt_1^{(1)} \dots dt_{k_1}^{(1)} \dots dt_{k_N}^{(N)}. \quad (22)$$

The first discrimination value $I(T)$ thus derives according to the following rule:

$$\begin{aligned}
I(T) = & -\int p(\text{out}) \cdot \ln(p(\text{out})) dt_1^{(1)} \dots dt_{k_1}^{(1)} \dots dt_{k_N}^{(N)} + \\
& + \sum_{j=1}^S p_j \int p(\text{out}|s^{(j)}) \cdot \ln(p(\text{out}|s^{(j)})) dt_1^{(1)} \dots dt_{k_1}^{(1)} \dots dt_{k_N}^{(N)} \quad (23)
\end{aligned}$$

with

$$p(\text{out}) = \sum_{j=1}^S p_j p(\text{out}|s^{(j)}), \quad (24)$$

whereby

- $s^{(j)}$ references an input quantity that is applied to the neural network at a time j ,
- p_j references a probability that the input quantity $s^{(j)}$ is applied to the neural network at a point in time j ,
- $p(\text{out}|s^{(j)})$ references a conditioned probability that a pulse is generated by a pulsed neuron in the neural network under the condition that the input quantity $s^{(j)}$ is applied to the neural network at a point in time j .

When a maximum first discrimination value $I(T)$ has been determined in the framework of training the neural network 301, then this means that the input pattern 306, 307, 308 observed in the first time span contains enough information in order to classify the input pattern with adequate dependability.

The first discrimination value $I(T)$ is clearly formed (step 101) in the framework of the training for a first time span $[0; T]$ (see **Figure 1**).

In a further step (step 102), a second time span is formed by shortening the first time span: $[0; T']$, whereby $T' < T$ applies.

For the second time span $[0; T']$, a second discrimination value $I(T')$ is formed in a further step (step 103) in the same way as described above for the first discrimination value $I(T)$.

The first discrimination value $I(T)$ is compared to the second discrimination value $I(T')$ (step 104).

When the second discrimination value $I(T')$ is the same as the first discrimination value $I(T)$, then a new second time span is formed (step 105) by shortening the second time span $[0; T']$, and the new second time span is considered to be the second time span (step 106). A second discrimination value $I(T')$ is in turn
 5 formed (step 103) for the second time span of the new iteration.

Clearly, this iterative method means that the time span wherein pulses generated by the pulsed neurons are taken into consideration for forming the output signal is shortened until the second discrimination value $I(T')$ is unequal to the first discrimination value $I(T)$.

10 When the second discrimination value $I(T')$ is smaller than the first discrimination value, then the neural network 301 is viewed as being an optimized neural network that was trained in the last preceding iteration wherein the second discrimination value $I(T')$ was not smaller than the first discrimination value $I(T)$ (step 107).

15 The time span respectively taken into consideration is divided into discrete time sub-spans for which the only thing respectively determined is whether a neuron generated a pulse during the time sub-span or not.

In this way, the calculating outlay needed for the training is considerably reduced.

20 For further illustration, the principle is explained again on the basis of **Figure 4.**

Figure 4 shows two continuous processes $p1$ and $p2$ that are formed by a set of continuous input signals $S1$ and $S2$. Two sequences of input quantities, the input patterns, are present after a corresponding, above-described digitalization. The
 25 input patterns are supplied to the trained neural network 401 in an application phase, and a space-time encoding of the processes $p1$, $p2$ is clearly implemented on the basis of the time rows for the trained neural network 401.

On the basis of an output signal 402, the trained neural network 401 indicates the kind of process the input pattern involves. The trained neural network
 30 401 exhibits the property that, first, the dependability of the optimization is optimized

and, second, a minimum plurality of time row values, i.e. a minimum second time span 403, is required in order to dependably implement the classification.

A few alternatives to the above-described exemplary embodiment are present below:

- 5 The plurality of inputs, of pulsed neurons as well as output signals is generally arbitrary. The plurality of different sequences of time row values is also arbitrary in the framework of the classification and in the framework of the training. An electroencephalogram analysis is thus possible for an arbitrary plurality of channels for characterizing tumors.

The following publications have been cited in this document:

- [1] G. Deco and B. Schürmann, Information Transmission and Temporal Code in Central Spiking Neurons, Physical Review Letters, Vol. 79, No. 23, pp. 4697-4700, December 1997
- 5 [2] W. Gerstner, Time structure of the activity in neural network models, Physical Review E, Vol. 51, No. 1, pp. 738-758, January 1995
- [3] K. P. Unnikrishnan and K. P. Venugopal, Alopex: A Correlation-Based Learning Algorithm for Feedforward and Recurrent Neural Networks, pp. 471-490, Neural Computation, Vol. 6, 1994
- 10 [4] DE 195 31 967 C2

Patent Claims

1. Method for training a neural network that contains pulsed neurons,
 - a) the neural network is trained such for a first time span ($[0; T]$) that a discrimination value is maximized, as a result whereof a maximum first discrimination value is formed;
 - b) the discrimination value is formed dependent on pulses that are formed by the pulsed neurons within the first time span as well as on a training sequence of input quantities that are supplied to the neural network;
 - c) the following steps are interactively implemented:
 - the first time span is shortened to form a second time span,
 - a second discrimination value is formed for the second time span,
 - when the second discrimination value is the same as the first discrimination value, then a new iteration ensues with a new second time span that is formed by shortening the second time span of the preceding iteration,
 - otherwise, the method is ended and the trained neural network is the neural network of the last iteration wherein the second discrimination value is the same as the first discrimination value.

2. Method according to claim 1, whereby an optimization method that is not gradient based is utilized for the maximization of the first discrimination value and/or of the second discrimination value.

3. Method according to claim 2, whereby the optimization method is based on the ALOPEX method.

4. Method according to one of the claims 1 through 3, whereby the first discrimination value $I(T)$ satisfies the following rule:

$$I(T) = I\left(s; \left\{ \begin{array}{l} t_1^{(1)}, \dots, t_m^{(1)}, \dots, t_{k_1}^{(1)}, t_1^{(2)}, \dots, t_m^{(2)}, \dots, t_{k_2}^{(2)}, \dots, \\ t_1^{(n)}, \dots, t_m^{(n)}, \dots, t_{k_n}^{(n)}, \dots, t_1^{(N)}, \dots, t_m^{(N)}, \dots, t_{k_N}^{(N)} \end{array} \right\} \right),$$

whereby

- s references the input quantities,

- 5

$I(T)$ satisfies the following rule:

$$\begin{aligned} \mathbb{I}(T) = & -\int p(\text{out}) \cdot \ln(p(\text{out})) dt_1^{(1)} \dots dt_{k_1}^{(1)} \dots dt_{k_N}^{(N)} + \\ & + \sum_{j=1}^S p_j \int p(\text{out}|s^{(j)}) \cdot \ln(p(\text{out}|s^{(j)})) dt_1^{(1)} \dots dt_{k_1}^{(1)} \dots dt_{k_N}^{(N)} \end{aligned}$$

with

$$p(\text{out}) = \sum_{j=1}^S p_j p(\text{out} | s^{(j)}),$$

whereby

- 10

15

6. Method according to one of the claims 1 through 5, whereby the training sequence of inputs quantities are [sic] measured physical signals.

7. Method according to claim 6, whereby the training sequence of input quantities are [sic] signals of an electroencephalogram.

8. Method for the classification of a sequence of input quantities upon employment of a neural network that contains pulsed neurons and was trained according to the following steps:

- a) the neural network is trained such for a first time span that a discrimination value is maximized, as a result whereof a maximum first discrimination value is formed;
- b) the discrimination value is formed dependent on pulses that are formed by the pulsed neurons within the first time span as well as on a training sequence of input quantities that are supplied to the neural network;
- c) the following steps are interactively implemented:
 - the first time span is shortened to form a second time span,
 - a second discrimination value is formed for the second time span,
 - when the second discrimination value is the same as the first discrimination value, then a new iteration ensues with a new second time span that is formed by shortening the second time span of the preceding iteration,
 - otherwise, the method is ended and the trained neural network is the neural network of the last iteration wherein the second discrimination value is the same as the first discrimination value,
- whereby the sequence of input quantities is supplied to the neural network;
- whereby a classification signal is formed that indicates what kind of sequence of input quantities the supplied sequence is.

9. Method according to claim 9, whereby the training sequence of input quantities and the sequence of input quantities are measured physical signals.

10. Method according to claim 9, whereby the training sequence of input quantities and the sequence of input quantities are measured signals of an electroencephalogram.

11. Neural network that contains pulsed neurons has been trained according to the following steps:

- a) the neural network is trained such for a first time span that a discrimination value is maximized, as a result whereof a maximum first discrimination value is formed;
- b) the discrimination value is formed dependent on pulses that are formed by the pulsed neurons within the first time span as well as on a training sequence of input quantities that are supplied to the neural network;
- c) the following steps are interactively implemented:
- the first time span is shortened to form a second time span,
 - a second discrimination value is formed for the second time span,
 - when the second discrimination value is the same as the first discrimination value, then a new iteration ensues with a new second time span that is formed by shortening the second time span of the preceding iteration,
 - otherwise, the method is ended and the trained neural network is the neural network of the last iteration wherein the second discrimination value is the same as the first discrimination value.
12. Neural network according to claim 10, utilized for the classification of a physical signal.
13. Neural network according to claim 10, utilized for the classification of a physical signal.
14. Arrangement for training a neural network that contains pulsed neurons comprises a processor that is configured such that the following steps can be implemented:
- a) the neural network is trained such for a first time span that a discrimination value is maximized, as a result whereof a maximum first discrimination value is formed;
- b) the discrimination value is formed dependent on pulses that are formed by the pulsed neurons within the first time span as well as on a training sequence of input quantities that are supplied to the neural network;
- c) the following steps are interactively implemented:
- the first time span is shortened to form a second time span,

-- a second discrimination value is formed for the second time span,
-- when the second discrimination value is the same as the first
discrimination value, then a new iteration ensues with a new second time
span that is formed by shortening the second time span of the preceding
iteration,

5

-- otherwise, the method is ended and the trained neural network is the
neural network of the last iteration wherein the second discrimination
value is the same as the first discrimination value.

15. Arrangement according to claim 14, utilized for the classification of a
10 physical signal.

16. Arrangement according to claim 14, utilized for the classification of a
signal of an electroencephalogram.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
219

Abstract

METHOD FOR TRAINING A NEURAL NETWORK, METHOD FOR THE
CLASSIFICATION OF A SEQUENCE OF INPUT QUANTITIES UPON
EMPLOYMENT OF A NEURAL NETWORK, NEURAL NETWORK AND
5 ARRANGEMENT FOR THE TRAINING OF A NEURAL NETWORK

For a first time span, the neural network is trained such that a
discrimination value is maximized, whereby the discrimination values is dependent on
pulses that are formed by pulsed neurons within the first time span. Iteratively, the
first time span is shortened and a second discrimination value is formed until the
10 second discrimination value is smaller than the maximum discrimination value. The
trained neural network is the neural network of the last iteration wherein the second
discrimination value is equal to the maximum discrimination value.

PCT
 WELTORGANISATION FÜR GEISTIGES EIGENTUM
 Internationales Büro
 INTERNATIONALE ANMELDUNG VERÖFFENTLICHT NACH DEM VERTRAG ÜBER DIE
 INTERNATIONALE ZUSAMMENARBEIT AUF DEM GEBIET DES PATENTWESENS (PCT)



(51) Internationale Patentklassifikation ⁷ : G06N 3/04	A3	(11) Internationale Veröffentlichungsnummer: WO 00/11601 (43) Internationales Veröffentlichungsdatum: 2. März 2000 (02.03.00)
(21) Internationales Aktenzeichen: PCT/DE99/01949 (22) Internationales Anmeldedatum: 1. Juli 1999 (01.07.99) (30) Prioritätsdaten: 198 38 654.0 25. August 1998 (25.08.98) DE (71) Anmelder (für alle Bestimmungsstaaten ausser US): SIEMENS AKTIENGESELLSCHAFT [DE/DE]; Wittelsbacherplatz 2, D-80333 München (DE). (72) Erfinder; und (75) Erfinder/Anmelder (nur für US): DECO, Gustavo [IT/DE]; Hauptstrasse 76, D-85579 Neubiberg (DE). SCHÜRMANN, Bernd [DE/DE]; Münchner Strasse 35, D-85778 Haimhausen (DE). (74) Gemeinsamer Vertreter: SIEMENS AKTIENGESELLSCHAFT; Postfach 22 16 34, D-80506 München (DE).	(81) Bestimmungsstaaten: US, europäisches Patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Veröffentlicht <i>Mit internationalem Recherchenbericht.</i> (88) Veröffentlichungsdatum des internationalen Recherchenberichts: 18. Mai 2000 (18.05.00)	

(54) Title: METHOD FOR TRAINING A NEURAL NETWORK, METHOD FOR CLASSIFYING A SEQUENCE OF INPUT PARAMETERS USING A NEURAL NETWORK, NEURAL NETWORK AND ARRAY FOR TRAINING A NEURAL NETWORK

(54) Bezeichnung: VERFAHREN ZUM TRAINIEREN EINES NEURONALEN NETZES, VERFAHREN ZUR KLASSIFIKATION EINER FOLGE VON EINGANGSGRÖSSEN UNTER VERWENDUNG EINES NEURONALEN NETZES, NEURONALES NETZ UND ANORDNUNG ZUM TRAINIEREN EINES NEURONALEN NETZES

(57) Abstract

The neural network is trained for a first period in such a way that a discrimination value is maximized, wherein the discrimination value is dependent on impulses formed by the pulsed neurons during the first period. The first period is shortened in an iterative manner and a second discrimination value is formed for the second period until the second discrimination value is smaller than the maximum discrimination value. The trained neural network is the neural network of the last iteration in which the second discrimination value equals the maximum discrimination value.

(57) Zusammenfassung

Für einen ersten Zeitraum wird das neuronale Netz derart trainiert, daß ein Unterscheidungswert maximiert wird, wobei der Unterscheidungswert abhängig ist von Impulsen, die von den gepulsten Neuronen innerhalb des ersten Zeitraums gebildet werden. Iterativ wird der erste Zeitraum so lange verkürzt und für den zweiten Zeitraum ein zweiter Unterscheidungswert gebildet, bis der zweite Unterscheidungswert kleiner ist als der maximale Unterscheidungswert. Das trainierte neuronale Netz ist das neuronale Netz der letzten Iteration, bei der der zweite Unterscheidungswert gleich dem maximalen Unterscheidungswert ist.




FIG 1




FIG 2






FIG 3





German Language Declaration

VERTRETUNGSVOLLMACHT: Als benannter Erfinder beauftrage ich hiermit den nachstehend benannten Patentanwalt (oder die nachstehend benannten Patentanwälte) und/oder Patent-Agenten mit der Verfolgung der vorliegenden Patentanmeldung sowie mit der Abwicklung aller damit verbundenen Geschäfte vor dem Patent- und Warenzeichenamt: (Name und Registrationsnummer anführen)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (list name and registration number)

And I hereby appoint

Messrs. John D. Simpson (Registration No. 19,842), Lewis T. Steadman (17,074), William C. Stueber (16,453), P. Phillips Connor (19,259), Dennis A. Gross (24,410), Marvin Moody (16,549), Steven H. Noll (28,982), Brett A. Valiquet (27,841), Thomas I. Ross (29,275), Kevin W. Guynn (29,927), Edward A. Lehmann (22,312), James D. Hobart (24,149), Robert M. Barrett (30,142), James Van Santen (16,584), J. Arthur Gross (13,615), Richard J. Schwarz (13,472) and Melvin A. Robinson (31,870), David R. Metzger (32,919), John R. Garrett (27,888) all members of the firm of Hill, Steadman & Simpson, A Professional Corporation.

Telefongespräche bitte richten an:
(Name und Telefonnummer)

Direct Telephone Calls to: (name and telephone number)

312/876-0200
Ext. _____

Postanschrift:

Send Correspondence to:

HILL, STEADMAN & SIMPSON
A Professional Corporation
85th Floor Sears Tower, Chicago, Illinois 60606

<p>Voller Name des einzigen oder ursprünglichen Erfinders: DECO, Gustavo</p>	<p>Full name of sole or first inventor: DECO, Gustavo</p>
<p>Unterschrift des Erfinders Datum 19.6.99</p>	<p>Inventor's signature Date 19.6.99</p>
<p>Wohnsitz DE 4 D-85579 Neubiberg, Germany</p>	<p>Residence D-85579 Neubiberg, Germany</p>
<p>Staatsangehörigkeit Italien</p>	<p>Citizenship Italien</p>
<p>Postanschrift Hauptstr. 76</p>	<p>Post Office Address Hauptstr. 76</p>
<p>D-85579 Neubiberg</p>	<p>D-85579 Neubiberg</p>
<p>Bundesrepublik Deutschland</p>	<p>Bundesrepublik Deutschland</p>

<p>Voller Name des zweiten Miterfinders (falls zutreffend): SCHÜRMANN, Bernd</p>	<p>Full name of second joint inventor, if any: SCHÜRMANN, Bernd</p>
<p>Unterschrift des Erfinders Datum 14.06.99</p>	<p>Second Inventor's signature Date 14.06.99</p>
<p>Wohnsitz DE 4 D-85778 Haimhausen, Germany</p>	<p>Residence D-85778 Haimhausen, Germany</p>
<p>Staatsangehörigkeit Bundesrepublik Deutschland</p>	<p>Citizenship Bundesrepublik Deutschland</p>
<p>Postanschrift Münchner Str. 35</p>	<p>Post Office Address Münchner Str. 35</p>
<p>D-85778 Haimhausen</p>	<p>D-85778 Haimhausen</p>
<p>Bundesrepublik Deutschland</p>	<p>Bundesrepublik Deutschland</p>

(Bitte entsprechende Informationen und Unterschriften im Falle von dritten und weiteren Miterfindern angeben).

(Supply similar information and signature for third and subsequent joint inventors).

German Language Declaration

Prior foreign applications
Priorität beansprucht

Priority Claimed

198 38 654.0 Germany 25. August 1998
(Number) (Country) (Day Month Year Filed)
(Nummer) (Land) (Tag Monat Jahr eingereicht)

☒ ☐
Yes No
Ja Nein

(Number) (Country) (Day Month Year Filed)
(Nummer) (Land) (Tag Monat Jahr eingereicht)

☐ ☐
Yes No
Ja Nein

(Number) (Country) (Day Month Year Filed)
(Nummer) (Land) (Tag Monat Jahr eingereicht)

☐ ☐
Yes No
Ja Nein

Ich beanspruche hiermit gemäss Absatz 35 der Zivilprozessordnung der Vereinigten Staaten, Paragraph 120, den Vorzug aller unten aufgeführten Anmeldungen und falls der Gegenstand aus jedem Anspruch dieser Anmeldung nicht in einer früheren amerikanischen Patentanmeldung laut dem ersten Paragraphen des Absatzes 35 der Zivilprozessordnung der Vereinigten Staaten, Paragraph 122 offenbart ist, erkenne ich gemäss Absatz 37, Bundesgesetzbuch, Paragraph 1.56(a) meine Pflicht zur Offenbarung von Informationen an, die zwischen dem Anmeldedatum der früheren Anmeldung und dem nationalen oder PCT internationalen Anmeldedatum dieser Anmeldung bekannt geworden sind.

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §122, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application.

(Application Serial No.)
(Anmeldeseriennummer)

(Filing Date)
(Anmeldedatum)

(Status)
(patentiert, anhängig,
aufgegeben)

(Status)
(patented, pending,
abandoned)

(Application Serial No.)
(Anmeldeseriennummer)

(Filing Date)
(Anmeldedatum)

(Status)
(patentiert, anhängig,
aufgeben)

(Status)
(patented, pending,
abandoned)

Ich erkläre hiermit, dass alle von mir in der vorliegenden Erklärung gemachten Angaben nach meinem besten Wissen und Gewissen der vollen Wahrheit entsprechen, und dass ich diese eidesstattliche Erklärung in Kenntnis dessen abgebe, dass wissentlich und vorsätzlich falsche Angaben gemäss Paragraph 1001, Absatz 18 der Zivilprozessordnung der Vereinigten Staaten von Amerika mit Geldstrafe belegt und/oder Gefängnis bestraft werden können, und dass derartig wissentlich und vorsätzlich falsche Angaben die Gültigkeit der vorliegenden Patentanmeldung oder eines darauf erteilten Patentes gefährden können.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true, and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Declaration and Power of Attorney For Patent Application
Erklärung Für Patentanmeldungen Mit Vollmacht
German Language Declaration

Als nachstehend benannter Erfinder erkläre ich hiermit an Eides Statt:

As a below named inventor, I hereby declare that:

dass mein Wohnsitz, meine Postanschrift, und meine Staatsangehörigkeit den im Nachstehenden nach meinem Namen aufgeführten Angaben entsprechen,

My residence, post office address and citizenship are as stated below next to my name,

dass ich, nach bestem Wissen der ursprüngliche, erste und alleinige Erfinder (falls nachstehend nur ein Name angegeben ist) oder ein ursprünglicher, erster und Miterfinder (falls nachstehend mehrere Namen aufgeführt sind) des Gegenstandes bin, für den dieser Antrag gestellt wird und für den ein Patent beantragt wird für die Erfindung mit dem Titel:

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

Verfahren zum Trainieren eines neuronalen Netzes, Verfahren zur Klassifikation einer Folge von Eingangsgrößen unter Verwendung eines neuronalen Netzes, neuronales Netz und Anordnung zum Trainieren eines neuronalen Netzes

deren Beschreibung

the specification of which

(zutreffendes ankreuzen)

(check one)

☒ hier beigefügt ist.

☐ is attached hereto.

☐ am _____ als

☐ was filed on _____ as

PCT internationale Anmeldung

PCT international application

PCT Anwendungsnummer _____

PCT Application No _____

eingereicht wurde und am _____

and was amended on _____
(if applicable)

abgeändert wurde (falls tatsächlich abgeändert).

Ich bestätige hiermit, dass ich den Inhalt der obigen Patentanmeldung einschliesslich der Ansprüche durchgesehen und verstanden habe, die eventuell durch einen Zusatzantrag wie oben erwähnt abgeändert wurde.

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims as amended by any amendment referred to above.

Ich erkenne meine Pflicht zur Offenbarung irgendwelcher Informationen, die für die Prüfung der vorliegenden Anmeldung in Einklang mit Absatz 37, Bundesgesetzbuch, Paragraph 1.56(a) von Wichtigkeit sind, an.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a).

Ich beanspruche hiermit ausländische Prioritätsvorteile gemäss Abschnitt 35 der Zivilprozessordnung der Vereinigten Staaten, Paragraph 119 aller unten angegebenen Auslandsanmeldungen für ein Patent oder eine Erfindersurkunde, und habe auch alle Auslandsanmeldungen für ein Patent oder eine Erfindersurkunde nachstehend gekennzeichnet, die ein Anmeldedatum haben, das vor dem Anmeldedatum der Anmeldung liegt, für die Priorität beansprucht wird.

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed: